



# Christy's™

## — PRODUCT INFORMATION & SPECIFICATIONS —

### ULTRA SEAL™

#### DESCRIPTION

Ultra Seal™ is an all-purpose thread sealing compound, containing PTFE for easier assembly/disassembly. Ultra Seal™ is a white, brushable, grit-free, smooth paste. It provides a leak-free seal on most types of metal and plastic threaded applications. Ultra Seal™ is non-toxic, non-seizing, and non-hardening. There is no transfer of any taste or odor and it's non-corrosive. Ultra Seal™ contains an anti-galling compound that allows for easy disassembly after years of service.

#### APPLICATIONS

Ultra Seal™ will not transfer any taste or odor to the system being sealed. Excellent for food and water systems. It never hardens and is an anti-galling compound making it possible to disassemble pipes and bolts easily after many years. Acceptable for PVC, CPVC, ABS, ①Delrin®, ①Zytel®, Fiberglass, Nylon, Polypropylene, Polybutylene, Polyethylene, ②Celcon®, ③Cyclocac® and all types of metal applications.

#### SPECIFICATIONS & INDUSTRY LISTINGS

Ultra Seal™ is formulated with non-toxic inert oils and is free from any lead containing ingredients.

- Exceeds U.S. Federal Specification TT-S-1732. NSF Standard 14 / 61.
- Seals gas applications up to 3,000PSI (20,670 kPa) and liquids up to 10,000 PSI (68,900 kPa).
- Ultra Seal™ does not require any set or cure time, the system may be pressurized immediately after assembly.
- Ultra Seal™ is suitable for use in the following temperature ranges:

Gases:	-50°F (-46°C) to 400°F (204°C)
Liquids:	-50°F (-46°C) to 400°F (204°C)
Brushable:	-50°F (-46°C)



Ultra Seal™ Pipe Thread Sealant