

Runxin 63620

20m³ /hr Automatic Softener Valve

The 63620 automatic softener valves feature a flow rate of 20m³/h. It adopts a flat corrosion resistant gasket for opening and closing. The different functions of service, backwash, and fast rinsing can be made through simple parameter modification.



Material: The valve body is made of ABS plastic reinforced with 10% glass fibre, ensuring it is high impact resistant, heat resistant, and flame retardant. The valve core is made of a wear and corrosion resistant ceramic disc with a long service life and easy replacement.

Features:

1. Easy to install

2. LED dynamic display

3. Long outage indicator, if power goes out all the setting data will be preserved, and the process will continue when the power supply is back to normal. The user will only need to reset the time.

4. Keyboard protection If there is no operation within one minute, the keyboard will automatically lock, thus preventing unintended operation.

5. Equipped with a relief valve. The valve will upload the pressure between the pump and the control valve, ensuring booster pump and valve safety when switching between flows.

6. All parameters can be adjusted based on your needs.

Model:	63520T / 63620T
Regeneration	Time Clock type / Meter type
Mount Type	Top Mount
Inlet/Outlet	2 M
Drain	1.5" M
Brine Line Connector	3/4" M
Mounting Base	4" 8NPSM
Riser pipe	1.5" D-GB
Flow rate	20m ³ /hr
Filter tank	30-42"
Water Pressurer	0.2-0.6Mpa
Water Temperature	5-50degC
Water Turbidity	<5FTU
Power Adaptor	Input AC100~240V/50~60Hz Output DC12V/1.5A
Application	Residential softener, Boiler water softener, RO pretreatment
Filter Media	Softener Resin