

Medium Duty PVC Layflat

Waterequip Medium Duty PVC Blue Layflat is designed for water drainage at open pit mining and at civil engineering/dam construction sites in mountains or other areas where water must be moved to significantly higher or lower elevations. This hose has excellent abrasion resistance.



- Medium Duty Sunny Blue PVC Layflat

Special Features

- Abrasion resistant
- UV stabilised

Hose Construction

- **Tube** Blue PVC
- **Reinforcing** High strength textile
- **Cover** Blue PVC

Hose Length








- 100 meter coils

Working Pressure

- 70 - 150 psi

Temperature

- -20°C to 54°C

| Part Number | | Dimension (mm) | | Working Pressure | Burst Pressure | Weight | Coil Length | Outside Flat |
|-------------------------|----------------------------|---|---|---|--|---|---|---|
| | |  |  |  |  |  |  |  |
| per mtr | coil | Hose ID | Hose OD | PSI | PSI | kg/m | meters | mm |
| LFAB025 | LFAB025100 | 26.00 | 29.00 | 100 | 300 | .16 | 100 | 43 |
| LFAB032 | LFAB032100 | 33.00 | 35.00 | 100 | 300 | .20 | 100 | 53 |
| LFAB040 | LFAB040100 | 40.00 | 43.00 | 75 | 220 | .21 | 100 | 65 |
| LFAB050 | LFAB050100 | 52.00 | 55.00 | 75 | 220 | .29 | 100 | 84 |
| LFAB065 | LFAB065100 | 65.00 | 68.00 | 60 | 180 | .40 | 100 | 105 |
| LFAB080 | LFAB080100 | 77.00 | 82.00 | 60 | 180 | .75 | 100 | 125 |
| LFAB100 | LFAB100100 | 103.00 | 107.00 | 60 | 180 | .75 | 100 | 165 |
| LFAB125 | LFAB125100 | 128.00 | 132.00 | 45 | 135 | 1 | 100 | 205 |
| LFAB150 | LFAB150100 | 153.00 | 158.00 | 45 | 135 | 1.25 | 100 | 245 |
| LFAB200 | LFAB200100 | 207.00 | 212.00 | 45 | 135 | 1.93 | 100 | 330 |

Waterequip

072104 7973

Sales@waterequip.com.au

waterequip.com.au