

The WERO range of Reverse Osmosis machines are very impressive pieces of equipment and have standard feature that most imported machines don't offer. WERO standard features include Stainless steel frames, Australian standard compliant electrical system, Danfos pressure switches, Grundfos or Lowara pump options, ROC controllers, and Schedule 80 pipework and fittings.

WERO 4

- 200-2000L/hr
- 1-8 x 4040 membrane housings
- 20" x 4" pre-filter housing
- 304 stainless frame, pump, SS316 optional
- FRP housing or 304 stainless housing, SS316 optional
- Schedule 80 uPVC pipe
- WERO ROC controller & conductivity meter
- 240V or 380V supply
- Main Isolation switch – interlock on door
- Barrel unions pre and post components
- Adjustable leveling feet
- Flow adjustable needle valves
- Float level control option standard
- Manual override switches in control panel
- Low pressure feed safety switch
- High pressure membrane safety switch
- RO flush and recovery adjustable
- Recirculation option standard
- CIP connections



Image: WERO4-4

| WERO Size | WERO4-1 | WERO4-2 | WERO4-4 | WERO4-6 | WERO4-8 |
|----------------|----------|----------|-----------|----------|----------|
| Temperature | 20deg | 20deg | 20deg | 20deg | 20deg |
| No Membranes | 1 | 2 | 4 | 6 | 8 |
| Permeate Flow | 200-250L | 400-500L | 900-1000L | 1500L | 2000L |
| Pump Size | .75kw | .75kw | 1.1kw | 1.5kw | 2.2kw |
| Water Quality | >2000TDS | >2000TDS | >2000TDS | >2000TDS | >2000TDS |
| Salt Rejection | 99% | 99% | 99% | 99% | 99% |

Performance will vary depending on raw water quality and temperature